SECTION 1 Identification of the substance/mixture and of the company/undertaking

Product identification used on label:

Product identifier: SG-500B

Other means of identification:

Synonyms: None Chemical family: Mixture

Recommended use of the chemical and restrictions on use:

Recommended use: Corrosion Preventive Compound

Restrictions on use:Uses other than those described above

Name, address, and telephone number of the chemical The Scharpf Group, Inc manufacturer, importer, or other responsible party:

3791 Pickett Rd.
Oshkosh, WI 54904

Telephone number:

Email address: 920-233-7146 info@sgrpi.com

Emergency telephone number: ChemTel: 800-255-3924 (US and Canada)

ChemTel: 01800-099-0731 (Mexico)

SECTION 2 Hazards identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols:

GHS Classification: Flammable Liquid Category 3

Signal Word: Warning

Hazard Flammable liquid and vapor

Statements:

Unclassified None identified

Hazards (HNOC):

Precautionary Statements:

Prevention: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Keep container closed tightly.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wear protective gloves/protective clothing/eye protection/face protection.

Response: If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

In case of fire: Use appropriate media to extinguish.

Storage: Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Disposal: Dispose of contents/container to a suitable disposal site in accordance with

local/national/international regulations.

Hazards not otherwise classified:

No data available.

SECTION 3 Composition/information on ingredients

Chemical Name	Common name and synonyms	CA #	%
Distillates (Petroleum),	None	64742-47-8	44
Hydrotreated light			

Specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 First aid measures

 $\label{lem:condition} \textbf{Description of necessary measures, subdivided according to the different routes of }$

exposure, i.e., inhalation, skin and eye contact, and ingestion:

Inhalation: If symptoms are experienced remove source of contamination or move victim to fresh air

and obtain medical advice.

Eye Contact: Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head

to prevent chemical from transferring to the uncontaminated eye. Get immediate medical

attention.

Skin Contact: Wash with soap and water. Get medical attention if irritation develops or persists.

Safety Data Sheet SG-500B / Revision 27 / 2024-03-11 / R Handy

Page 2 of 11

Ingestion: Do not induce vomiting and seek medical attention immediately. Provide medical care

provider with this SDS. If vomiting occurs, lean victim forward to reduce risk of aspiration

into lungs.

Most important symptoms/effects, acute and delayed:

See Section 11

Indication of immediate medical attention and special treatment needed, if necessary:

Consult a physician. Treat symptomatically.

SECTION 5 Firefighting measures

Suitable (and unsuitable) extinguishing

media:
Suitable extinguishing media:

Use alcohol resistant foam, carbon dioxide, dry chemical or water spray when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the fire.

Unsuitable extinguishing media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical:

Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back. Empty containers that retain product residue (liquid, solid/sludge, or vapor) can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury or death.

Hazardous combustion products:

Carbon dioxide, Carbon monoxide, Sulfur oxides.

Special protective equipment and precautions for fire-fighters:

Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Use appropriate methods for the surrounding fire.

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures:

No health effects expected from the clean-up of this material, if contact can be avoided. Follow personal protective equipment

recommendations found in Section 8 of this SDS.

Methods and materials for containment

and cleaning up:

Absorb or cover with dry earth, sand or other non-combustible material and transfer to appropriate waste containers. Use clean, non-sparking tools to collect absorbed material. Collect and discard in

accordance with local, state and national regulations.

SECTION 7 Handling and storage

Precautions for safe handling:

Mildly irritating material. Avoid unnecessary exposure. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Do not get in eyes, on skin and clothing. Wash thoroughly after handling. As with all chemicals, good industrial hygiene practices should be followed when handling this material.

Conditions for safe storage,

Safe storage conditions:

including any

incompatibilities:

Store in a cool dry place. Isolate from incompatible materials. Keep away from

heat, sparks, and flame. Keep container closed when not in use.

Materials to Avoid/Chemical Incompatibility: Strong oxidizing agents

SECTION 8 Exposure controls/personal protection

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

Chemical component	OSHA PEL	ACGIH TLV	ACGIH STEL	IDLH
Distillates		200 mg/m3		No data available
(Petroleum),				
Hydrotreated light				

Appropriate engineering controls:

Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure.

Engineering controls must be designated to meet the OSHA chemical specific standard in 29 CFR 1910.

Individual protection measures, such as personal protective equipment:

Respiratory Protection: Respiratory protection may be required to avoid overexposure when handling this

product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate

symptoms.

Respirator Type(s): NIOSH approved purifying respirator with organic vapor cartridge.

Eye Protection: Wear chemically resistant safety glasses with side shields when handling this product.

Do not wear contact lenses.

When handling material that is heated, wear chemically resistant safety glasses with

side shields and a face shield.

Skin Protection: Wear protective gloves. Inspect gloves for chemical break-through and replace at

regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving

work.

Gloves: Chemically resistant gloves. When handling material that is heated, wear thermally

protective heat insulating chemically resistance gloves. If contact with forearms is

likely, wear gauntlet style gloves.

Other protective equipment:

Wear chemically resistant safety glasses with side shields when handling this product.

Do not wear contact lenses.

Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving

work.

When handling material that is heated, wear chemically resistant safety glasses with

side shields and a face shield.

General hygiene conditions:

Use with adequate ventilation. Do not use pressure to empty container. Ground and bond containers when transferring material. Use spark-proof tools and explosion-proof equipment. Follow all protective equipment recommendations provided in Section 8. Remove contaminated clothing and wash before reuse. Avoid contact with material, avoid breathing dusts or fumes, use only in a well-ventilated area. Prevent small spills and leakage to avoid slip hazard. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Do not get in eyes, on skin and clothing. Wash thoroughly after handling. As with all chemicals, good industrial

hygiene practices should be followed when handling this material.

SECTION 9 Physical and chemical properties (Typical, not specification)

Appearance (physical state, color, etc.):

Physical State: Viscous Liquid

Color: Black Odor: Mild

Merosene like
Odor Threshold:
No data available

pH: No data available

Melting point/freezing point (°C):

Melting Point, (°C):

Freezing Point, (°C):

Initial boiling point and boiling range

No data available

No data available

(°C):

Flash Point: >= 105 °F (41 °C)
Evaporation Rate: No data available
Flammability (Solid, Gas): No data available

Upper/Lower flammability or

explosive limits:

Upper flammable or explosive limits: No data available Lower flammable or explosive limits: No data available Vapor pressure: No data available > 2 mmHg @ 20°C

Vapor density: >1 (Air=1)
Relative density: .72

Solubility(ies):

Partition coefficient: n-octanol/water:

Auto-ignition temperature (°C):

Negligible; 0-1%

No data available

No data available

No data available

Viscosity: 4,000 – 9,000 cP

Volatiles, % by weight: 44
VOC, Material, lb/gal: 2.6
VOC, Material, grams/liter: 316
VOC minus exempt solvents & water, 316

grams/liter:

SECTION 10 Stability and reactivity

Reactivity: Not expected to be reactive.

Chemical stability: Hazardous polymerization will not occur.

Possibility of hazardous reactions: Under normal conditions of storage and use, hazardous

reactions will not occur.

Conditions to avoid (e.g. static discharge, shock

or vibration):

Temperature above flash point in combination with sparks,

open flames, or other sources of ignition. Elevated

temperatures. Contamination.

Incompatible materials: Strong oxidizing agents.

Hazardous decomposition products: Under normal conditions of use & storage, decomposition and

hazardous decomposition products are unlikely.

SECTION 11 Toxicological information

Description of the various toxicological (health) effects and the available data used to identify those effects:

Information on the likely routes of

exposure (inhalation, ingestion, skin and

eye contact):

Eye contact, Skin contact, Inhalation

Symptoms related to the physical,

chemical and toxicological characteristics:

No data available

Delayed and immediate effects and also chronic effects from short- and long-term exposure:

Ingestion Toxicity: Harmful if swallowed. Estimated to be >5.0 g/kg; practically non-toxic.

Skin Contact: Can cause minor skin irritation, defatting, and dermatitis.

Inhalation Toxicity: No data available

Eye Contact: Can cause moderate irritation, tearing and reddening, but not likely to permanently

injure eye tissue.

Sensitization: None know.

Mutagenicity: No data.

Reproductive and

Developmental

Toxicity:

No data available.

Carcinogenicity: There are no carcinogenic ingredients present at or over 0.1%.

STOT-single exposure: Based on available data, the classification criteria are not met.

STOT-repeated

exposure:

Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

Numerical measures of toxicity (such as acute toxicity estimates):

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Distillates (Petroleum),			Inhalation LC50 (4h) Rat >
Hydrotreated light			20 mg/L

Is the hazardous chemical listed in the National Toxicology Program (NTP) Report or Carcinogens (latest edition) or has it been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA?

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
No component of this			
product present at levels			
greater than or equal to			
0.1% is identified as a			
known or anticipated			
carcinogen.			

SECTION 12 Ecological information

Ecotoxicity (aquatic and terrestrial, where available): No data available

Ecological Toxicity Data:

Chemical Name	CAS#	Aquatic EC50 Crustacea	Aquatic ER50 Algae	Aquatic LC50 Fish
No data available				

Persistence and degradability: No data

Bio accumulative potential: No data available

Mobility in soil: No data available

Other adverse effects (such as No data available

hazardous to the ozone layer):

SECTION 13 Disposal considerations

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging:

Spent or discarded material is a hazardous waste.

Dispose of by incineration following Federal, State, Local or Provincial

regulations.

Waste codes / waste designations: D001

SECTION 14 Transport information

Domestic Ground in containers Corrosion preventive/Non-Regulated

<= 119 gallon

Domestic Ground in containers NA1993, COMBUSTIBLE LIQUID, n.o.s., (Mineral Spirits), PG III

> 119 gallon

If shipped in any size container at temperatures greater than flash point:

UN3256, Elevated Temperature Liquid, Flammable, N.O.S., (Mineral Spirits), 3,

PG III

No

Shipping name for Export, Air

(IATA)

UN1268, PETROLEUM DISTILLATES, N.O.S., (Mineral Spirits), 3, PG III

Shipping name for Export, Sea

(IMDG)

UN1268, PETROLEUM DISTILLATES, N.O.S., (Mineral Spirits), 3, PG III

Marine Pollutant?

SECTION 15 Regulatory information

International Inventory

Country(s) or region		On inventory (yes/no)*	
Australia	Australian Inventory of Chemical Substances (AICS)	Yes	
Canada	Domestic Substances List (DSL)	No	
Canada	Non-Domestic Substances List (NDSL)	Yes	
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes	
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes	
Europe	European List of Notified Chemical Substances (ELINCS)	No	
Japan	Inventory of Existing and New Chemical Substances (ENCS)		
Korea	Existing Chemicals List (ECL)	Yes	
New Zealand	New Zealand Inventory	Yes	
Philippines	Philippines Inventory of Chemicals and Chemical Substances (PICCS)	No	
Taiwan	Taiwan Inventory	No	

United States & Puerto Rico	Toxic Substances Control Act	Yes
	(TSCA) Inventory	

^{*} A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or are unknown from listing on the inventory administered by the governing country(s).

Chemical Name	CAS#	Regulation	Percent
Ethylbenzene	100-41-4	Prop. 65 – Cancer	<0.1
Cumene	98-82-8	Prop. 65 – Cancer	TRACE
Naphthalene	91-20-3	Prop. 65 – Cancer TRACE	
Benzene	71-43-2	Prop. 65 – Cancer TRACE	
Crystalline silica	14808-60-7	Prop. 65 – Cancer	TRACE
Toluene	108-88-3	Prop. 65 –	TRACE
		Developmental and/or	
		Reproductive	
Benzene	71-43-2	Prop. 65 –	TRACE
		Developmental and/or	
		Reproductive	
Xylene	1330-20-7	CERCLA	<0.1
			RQ = 100 lbs.
Ethylbenzene	100-41-4	CERCLA	<0.1
			RQ = 1,000 lbs.
Toluene	108-88-3	CERCLA	TRACE
- "		<u> </u>	RQ = 1,000 lbs.
Sodium hydroxide	1310-73-2	CERCLA	TRACE
•	00.02.0	CERCIA .	RQ = 1,000 lbs.
Cumene	98-82-8	CERCLA	TRACE
Nambah alama	04.20.2	CERCIA	RQ = 5,000 lbs.
Naphthalene	91-20-3	CERCLA	TRACE
Donnana	71-43-2	CERCLA	RQ = 100 lbs. TRACE
Benzene	/1-43-2	CERCLA	RQ = 10 lbs.
Cobolt Compounds	68553-15-1	SARA 313	1-5
(N096)	00333-13-1	3ANA 313	1-3
Xylene	1330-20-7	SARA 313	<0.1
Ethylbenzene	100-41-4	SARA 313	<0.1
Toluene	108-88-3	SARA 313	TRACE
Cumene	98-82-8	SARA 313	TRACE
Naphthalene	91-20-3	SARA 313	TRACE
Benzene	71-43-2	SARA 313	TRACE
No SARA 302 EHS-listed		SARA EHS	
chemicals in this			
product.			

SECTION 16 Other information

SDS Prepared by: R Handy

Revision Date: March 11, 2024

Revision Number: 27

Reason for revision: Reviewed

Approved: R Handy

Disclaimer: Although the information contained herein is believed to be reliable, it is furnished

without warranty of any kind. This information is not intended to be all-inclusive as to the

manner and conditions of use, handling, and storage.