#### SECTION 1 Identification of the substance/mixture and of the company/undertaking

Product identification used on label:

Product identifier: SG-50A

Other means of identification:

Synonyms: None Chemical family: Mixture

Recommended use of the chemical and restrictions on use:

Recommended use:Corrosion Preventive CompoundRestrictions on use:Uses other than those described above

Name, address, and telephone number of the chemical The Scharpf Group, Inc manufacturer, importer, or other responsible party: 3791 Pickett Rd.
Oshkosh, WI 54904

Telephone number:

**Email address:** 920-233-7146 / 920-233-0353 FAX

info@sgrpi.com

**Emergency telephone number:** ChemTel: 800-255-3924 (US and Canada)

ChemTel: 01800-099-0731 (Mexico)

#### **SECTION 2 Hazards identification**

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols:





GHS Classification: Skin Corrosion/Irritation Category 2; Flammable Liquid Category 3; Specific Target Organ

Systemic Toxicity (STOT) – Single Exposure Category 3; Hazardous to the aquatic

environment - Acute Category 3

Signal Word: Warning

**Hazard** Flammable liquid and vapor.

**Statements:** 

Causes skin and eye irritation.

**Unclassified** None identified

Hazards (HNOC):

Precautionary Statements:

**Prevention:** Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

**Response:** If on skin: Wash with plenty of soap and water.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell. Specific treatment: See Section 4 of this SDS.

If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.

**Storage:** Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

**Disposal:** Dispose of contents/container to a suitable disposal site in accordance with

local/national/international regulations.

Hazards not otherwise classified:

No data available.

#### **SECTION 3 Composition/information on ingredients**

\_\_\_\_\_\_\_

Chemical Name	Common name and	CA #	%
	synonyms		
Hydrotreated light	None	64742-47-8	42
distillates (Petroleum)			

Specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

#### **SECTION 4 First aid measures**

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion:

**Inhalation:** Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If

not breathing, give artificial respiration and have a trained individual administer oxygen.

Get medical attention immediately.

**Eye Contact:** Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head

to prevent chemical from transferring to the uncontaminated eye. Get immediate medical

attention.

**Skin Contact:** Wash with soap and water. Get medical attention if irritation develops or persists.

**Ingestion:** Do not induce vomiting and seek medical attention immediately. Provide medical care

provider with this SDS. If vomiting occurs, lean victim forward to reduce risk of aspiration

into lungs.

Most important symptoms/effects, acute and delayed:

Causes skin irritation. May cause drowsiness or dizziness.

Indication of immediate medical attention and special treatment needed, if

necessary:

Consult a physician. Treat symptomatically.

#### **SECTION 5 Firefighting measures**

Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media: Use alcohol resistant foam, carbon dioxide, dry chemical or water spray

when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully

applied to the fire.

**Unsuitable extinguishing media:** Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical:

Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back. Empty containers that retain product residue (liquid, solid/sludge, or vapor) can be

dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may

lead to injury or death.

**Hazardous combustion products:** Carbon dioxide, Carbon monoxide, Sulfur oxides.

Special protective equipment and precautions for fire-fighters:

Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Use appropriate methods for the surrounding

fire.

#### **SECTION 6 Accidental release measures**

**Personal precautions, protective**No health effects expected from the clean-up of this material, if equipment and emergency procedures: contact can be avoided. Follow personal protective equipment

recommendations found in Section 8 of this SDS.

Methods and materials for containment and cleaning up:

Absorb or cover with dry earth, sand or other non-combustible material and transfer to appropriate waste containers. Use clean, non-sparking tools to collect absorbed material. Collect and discard in accordance with local, state and national regulations.

#### **SECTION 7 Handling and storage**

Precautions for safe handling: Mildly irri

Mildly irritating material. Avoid unnecessary exposure. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Ground and bond containers when transferring material. Do not get in eyes, on skin and clothing. Wash thoroughly after handling. As with all chemicals, good industrial hygiene practices should be followed when handling this material.

Conditions for safe storage,

including any

incompatibilities: Store in a cool dry place. Isolate from incompatible materials. Keep away from

Safe storage conditions: heat, sparks, and flame. Keep container closed when not in use.

Materials to Avoid/Chemical Incompatibility: Strong oxidizing agents

#### **SECTION 8 Exposure controls/personal protection**

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

Chemical component	OSHA PEL	ACGIH TLV	ACGIH STEL	IDLH
Hydrotreated light		200 mg/m3	No data available	No data available
distillates				
(Petroleum)				

Appropriate engineering controls:

Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure.

Engineering controls must be designated to meet the OSHA chemical specific standard in 29 CFR 1910.

Individual protection measures, such as personal protective equipment:

**Respiratory Protection:** Respiratory protection may be required to avoid overexposure when handling this

product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate

symptoms.

**Respirator Type(s):** NIOSH approved purifying respirator with organic vapor/acid gas cartridge.

**Eye Protection:** Wear chemically resistant safety glasses with side shields when handling this product.

Do not wear contact lenses.

**Skin Protection:** Wear protective gloves. Inspect gloves for chemical break-through and replace at

regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving

work.

**Gloves:** Chemically resistant gloves.

Other protective equipment:

Wear chemically resistant safety glasses with side shields when handling this product.

Do not wear contact lenses.

Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving

work.

General hygiene conditions:

Use with adequate ventilation. Do not use pressure to empty container. Remove contaminated clothing and wash before reuse. Avoid contact with material, avoid breathing dusts or fumes, use only in a well-ventilated area. Follow all protective equipment recommendations provided in Section 8. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Ground and bond containers when transferring material. Do not get in eyes, on skin and clothing. Wash thoroughly after handling. As with all chemicals, good industrial hygiene practices should be followed when handling this material.

#### **SECTION 9 Physical and chemical properties (Typical, not specification)**

Appearance (physical state, color, etc.):

Physical State: Viscous Liquid

Color: Tan Odor: Mild

Kerosene like

Odor Threshold: No data available pH: No data available

Melting point/freezing point (°C):

Melting Point, (°C):No data availableFreezing Point, (°C):No data availableInitial boiling point and boiling rangeNo data available

(°C):

Flash Point: >= 105 °F (41 °C)
Evaporation Rate: No data available
Flammability (Solid, Gas): No data available

Upper/Lower flammability or

explosive limits:

Upper flammable or explosive limits: No data available
Lower flammable or explosive limits: No data available
Vapor pressure: > 2 mmHg @ 20°C

Vapor density: >1 (Air=1)
Relative density: .943

Solubility(ies):

Partition coefficient: n-octanol/water:
Auto-ignition temperature (°C):

Decomposition temperature (°C):

Viscosity:

Negligible; 0-1%

No data available

No data available

4000 - 9000 cP

Volatiles, % by weight: 42
VOC, Material, lb/gal: 3.25
VOC, Material, grams/liter: 395
VOC minus exempt solvents & water, 395

grams/liter:

#### **SECTION 10 Stability and reactivity**

**Reactivity:** Not expected to be reactive.

**Chemical stability:** Hazardous polymerization will not occur.

**Possibility of hazardous reactions:** Under normal conditions of storage and use, hazardous

reactions will not occur.

Conditions to avoid (e.g. static discharge, shock

or vibration):

Temperature above flash point in combination with sparks,

open flames, or other sources of ignition. Elevated

temperatures. Contamination.

**Incompatible materials:** Strong oxidizing agents.

**Hazardous decomposition products:** Under normal conditions of use & storage, decomposition and

hazardous decomposition products are unlikely.

#### **SECTION 11 Toxicological information**

Description of the various toxicological (health) effects and the available data used to identify those effects:

Information on the likely routes of

exposure (inhalation, ingestion, skin and

eye contact):

Eye contact, Skin contact, Inhalation

**Symptoms related to the physical,** Causes skin irritation. May cause drowsiness or

chemical and toxicological characteristics: dizziness.

Delayed and immediate effects and also chronic effects from short- and long-term exposure:

Ingestion Toxicity: Harmful if swallowed. Estimated to be >5.0 g/kg; practically non-toxic.

**Skin Contact:** Can cause minor skin irritation, defatting, and dermatitis.

**Inhalation Toxicity:** No data available

**Eye Contact:** Can cause moderate irritation, tearing and reddening, but not likely to permanently

injure eye tissue.

**Sensitization:** None know.

Mutagenicity: No data.

Reproductive and Developmental

Toxicity:

No data available.

**Carcinogenicity:** There are no carcinogenic ingredients present at or over 0.1%.

STOT-single exposure: Classification has been based on toxicological information of the components in Section

3.

STOT-repeated

Based on available data, the classification criteria are not met.

exposure:

**Aspiration hazard:** Based on available data, the classification criteria are not met.

Numerical measures of toxicity (such as acute toxicity estimates):

<b>Chemical Name</b>	LD50 Oral	LD50 Dermal	LC50 Inhalation
Hydrotreated light			Inhalation LC50 (4h) Rat >
distillates (Petroleum)			20 mg/L

Is the hazardous chemical listed in the National Toxicology Program (NTP) Report or Carcinogens (latest edition) or has it been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA?

<u>, , , , , , , , , , , , , , , , , , , </u>	,, ,		
<b>Chemical Name</b>	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
No component of this			
product present at levels			
greater than or equal to			
0.1% is identified as a			
known or anticipated			
carcinogen.			

#### **SECTION 12 Ecological information**

Ecotoxicity (aquatic and terrestrial, where available): No data available

**Ecological Toxicity Data:** 

Chemical Name	CAS#	Aquatic EC50 Crustacea	Aquatic ER50 Algae	Aquatic LC50 Fish	
No data available		Crustaccu			

Persistence and degradability: No data

Bioaccumulative potential: No data available

Mobility in soil: No data available

Other adverse effects (such as No data available

hazardous to the ozone layer):

#### **SECTION 13 Disposal considerations**

Description of waste residues and information on their safe handling and methods of disposal, including the

Spent or discarded material is a hazardous waste.

disposal of any contaminated

packaging:

Dispose of by incineration following Federal, State, Local or Provincial

regulations.

Waste codes / waste designations: D001

#### **SECTION 14 Transport information**

**Domestic Ground in containers** 

Corrosion preventive/Non-Regulated

<= 119 gallon

**Domestic Ground in containers** 

> 119 gallon

NA1993, COMBUSTIBLE LIQUID, n.o.s., (Mineral Spirits), PG III

If shipped in any size container at temperatures greater than flash point:

UN3256, Elevated Temperature Liquid, Flammable, N.O.S., (Mineral Spirits), 3,

PG III

Shipping name for Export, Air

(IATA)

UN1268, PETROLEUM DISTILLATES, N.O.S., (Mineral Spirits), 3, PG III

Shipping name for Export, Sea

(IMDG)

UN1268, PETROLEUM DISTILLATES, N.O.S., (Mineral Spirits), 3, PG III

**Marine Pollutant?** No

#### **SECTION 15 Regulatory information**

#### Status of formula components on selected national regulatory inventories:

LIST	STATUS
TSCA	All components in this product are on the TSCA Inventory or exempt.
Canadian DSL	One or more chemical substance in this material are on the Canadian NSDL and the
	remainder are included on the Canadian DSL or are exempt.

Chemical Name	CAS#	Regulation	Percent
Ethylbenzene	100-41-4	Prop. 65 – Cancer	<0.1
Cumene	98-82-8	Prop. 65 – Cancer	TRACE
Naphthalene	91-20-3	Prop. 65 – Cancer	TRACE
Benzene	71-43-2	Prop. 65 – Cancer	TRACE
Toluene	108-88-3	Prop. 65 –	TRACE
		Developmental and/or	
		Reproductive	
Benzene	71-43-2	Prop. 65 –	TRACE
		Developmental and/or	
		Reproductive	
Xylene	1330-20-7	CERCLA	<0.1

			RQ = 100 lbs
Ethylbenzene	100-41-4	CERCLA	<0.1
			RQ = 1,000 lbs
Toluene	108-88-3	CERCLA	TRACE
			RQ = 1,000 lbs
Cumene	98-82-8	CERCLA	TRACE
			RQ = 5,000 lbs
Naphthalene	91-20-3	CERCLA	TRACE
			RQ = 100 lbs
Benzene	71-43-2	CERCLA	TRACE
			RQ = 10 lbs
Cobolt Compounds (N096)	68553-15-1	SARA 313	3-7
Xylene	1330-20-7	SARA 313	<0.1
Ethylbenzene	100-41-4	SARA 313	<0.1
Toluene	108-88-3	SARA 313	TRACE
Cumene	98-82-8	SARA 313	TRACE
Naphthalene	91-20-3	SARA 313	TRACE
Benzene	71-43-2	SARA 313	TRACE
No SARA 302 EHS-listed		SARA EHS	
chemicals in this			
product.			

#### **SECTION 16 Other information**

**SDS Prepared by:** R Handy

**Revision Date:** March 11, 2024

**Revision Number:** 25

Reason for revision: Reviewed

Approved: R Handy

**Disclaimer:** Although the information contained herein is believed to be reliable, it is furnished

without warranty of any kind. This information is not intended to be all-inclusive as to the

manner and conditions of use, handling, and storage.